



IDU-CPE

IDU-CPE is an indoor AC/DC PoE injector. It is designed only for R5000-Smn, R5000-Lmn and AUX-ODU-SYNC synchronization hub and has built-in lightning protection. PoE injector is powered by an AC supply in the 100-240 V range. Built-in lightning protection protects units connected to **IDU-CPE**.

Key Features

- ▶ Supplied by default with R5000-Lmn, R5000-Smn models and AUX-ODU-SYNC
- ▶ Indoors installations only
- ▶ Built-in lightning protection

IDU-CPE

Specifications

The compact unit design and its light weight ensure easy and rapid deployment. Mounting holes in the housing allow to securely fix **IDU-CPE** in the installation site.



Parameter	Description																								
Compatible models	R5000-Lmn , R5000-Smn, AUX-ODU-SYNC																								
Input Voltage (AC)	100 ... 240 V																								
Output Voltage	+ 48 V																								
Power Consumption	24 W																								
Ethernet Connectors Pin-out	<table border="1"> <thead> <tr> <th colspan="2">Ethernet IN:</th> <th colspan="2">Ethernet OUT:</th> </tr> <tr> <th>Pin</th> <th>Description</th> <th>Pin</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>Not connected</td> <td>4</td> <td>+VDC</td> </tr> <tr> <td>5</td> <td>Not connected</td> <td>5</td> <td>+VDC</td> </tr> <tr> <td>7</td> <td>Not connected</td> <td>7</td> <td>-VDC</td> </tr> <tr> <td>8</td> <td>Not connected</td> <td>8</td> <td>-VDC</td> </tr> </tbody> </table>	Ethernet IN:		Ethernet OUT:		Pin	Description	Pin	Description	4	Not connected	4	+VDC	5	Not connected	5	+VDC	7	Not connected	7	-VDC	8	Not connected	8	-VDC
	Ethernet IN:		Ethernet OUT:																						
Pin	Description	Pin	Description																						
4	Not connected	4	+VDC																						
5	Not connected	5	+VDC																						
7	Not connected	7	-VDC																						
8	Not connected	8	-VDC																						
IEC compatibility	EN61000-4																								
Operating temperature range	0...+40 °C																								
Size and Weight	87x78x36,5 mm, 0.15 kg																								

