


Quanta 5 Q5-23

| | |
|----------------------------------|--|
| Description | Quanta 5 Q5-23, 5 GHz point-to-point unit, net throughput up to 650 Mbps, integrated dual-pol antenna, 23 dBi, 10x10 deg |
| Net throughput | up to 650 Mbps |
| Recommended distances | up to 40 km |
| Radio technology | SC-FDE |
| Modulation coding schemes | from QPSK 1/4 to QAM256 7/8 |
| Transmit power | up to 27 dBm |
| Receiver sensitivity | down to -98 dBm |
| Frequency range | 4900-6000 MHz |
| Channel width | 3.5, 5, 7, 10, 14, 15, 20, 28, 30, 40, 50, 56 MHz |
| Center frequency adjustment step | 1 MHz |
| Duplex scheme | TDD |
| Antenna | 23 dBi |
| Wired Interfaces | 1x GigabitEthernet (RJ45) |



Quanta 5 Q5-23

| | |
|---------------------|--|
| Consumption | up to 15 W |
| Power options | 90-240 VAC ~ @ 50/60 Hz, ±43..56 VDC |
| Outdoor Unit (ODU) | 305 x 305 x 66 mm, 1.75 kg |
| |  |
| Part Number Example | Q5-23 |
| Packing List | <ul style="list-style-type: none"> - Outdoor unit Q5-23 - 1 pcs. - Power Supply IDU-CPE-G(24W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland - 1 pcs. - Standard RJ-45 connector - 1 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Cap - 1 pcs. - MONT-KIT-85 Mounting kit - 1 pcs. - Quick Start Guide - 1 pcs. |



Quanta 5 Q5-23

Features

RADIO

- ▶ **DFS**
 - ETSI/FCC, including radar detection (including off-channel CAC) and adaptivity
- ▶ **Instant DFS (pending)**
 - background spectrum monitoring by both Master and Slave terminal units
 - seamless channel change
- ▶ **Automatic Bitrate Control**
- ▶ **Automatic Transmit Power Control**
- ▶ **Channel Time Adjustment**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

MANAGEMENT FEATURES

- ▶ **Various Management Protocols: HTTP, SSH, HTTPS, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)**
- ▶ **Graphical User Interface**
- ▶ **LED Indication: power status, wireless and wired link status, signal level**
- ▶ **Antenna alignment tool**
- ▶ **Automatic software update**
- ▶ **Online monitoring with proprietary EMS InfiMONITOR**

QUALITY-OF-SERVICE

- ▶ **8 priority queues**
- ▶ **IEEE 802.1p support**
- ▶ **IP DiffServ support**



Quanta 5 Q5-23

Features

ENVIRONMENTAL

- ▶ Outdoor Units: -40..+60C, 100% humidity, condensing
- ▶ Indoor Unit: 0..+40C, 95% humidity, non-condensing

SECURITY FEATURES

- ▶ Storm/flood protection
- ▶ Password protection
- ▶ Secure command-line access via SSH protocol

MAC

- ▶ VLAN, 802.1ad DVLAN Q-in-Q (pending), 802.1Q (pending)

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN/IEC 62368-1:2014, UL 62368-1:2014
- ▶ **Radio:**
 - EN 301 893 v.2.1.1, EN 302 502, v.2.1.1, FCC part 15.407
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - RoHS3 Directive 2015/863/EU (pending)



Quanta 5 Q5-23

Radiation diagram

