


Um/5X.1000.4x150

Description	InfiLINK XG 1000 Um/5X.1000.4x150, 5 GHz point-to-point unit, net throughput up to 1000 Mbps, 2x N-type (F) connectors for external antenna
Net throughput	up to 1000 Mbps
Recommended distances	60+ km
Radio technology	MIMO 2x2, Cyclic single carrier
Modulation coding schemes	from QPSK 1/4 to QAM1024 8/10
Transmit power	up to 22 dBm
Receiver sensitivity	down to -93 dBm
Frequency range	4900-6000 MHz
Channel width	2x10, 2x20, 2x40 MHz
Center frequency adjustment step	1 MHz
Duplex scheme	TDD
Wired Interfaces	2x GigabitEthernet, SFP



Um/5X.1000.4x150

Consumption	up to 55 W
Power options	90-240 VAC @ 50/60 Hz, 43..56 VDC
Outdoor Unit (ODU)	
Packing List	<ul style="list-style-type: none"> - Outdoor unit Um/5X.1000.4x150 - 1 pcs. - Power Supply IDU-CPE-G(56W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland for RJ-45 - 2 pcs. - Cable Gland for optical cable - 1 pcs. - Standard RJ-45 connector - 2 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug C



Um/5X.1000.4x150

Features

RADIO

- ▶ **Best-in-breed spectral efficiency**
 - up to 12,5 bps/Hz
- ▶ **Flexible frequency planning**
 - utilizing two non-adjacent frequency channels
 - support of TDD and Hybrid-FDD
- ▶ **Reliable signal receiving in both LOS and NLOS conditions**
- ▶ **TDD synchronization using a built-in GNSS receiver**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting VLAN and STP**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

MANAGEMENT FEATURES

- ▶ **Web-based graphical user interface**
- ▶ **Command line interface**
- ▶ **SNMP v1/2c/3 support (MIB-II and proprietary MIBs)**
- ▶ **Centralized monitoring using EMS InfiMONITOR.**

QUALITY-OF-SERVICE

- ▶ **QoS support:**
 - 4 priority queues: strict and weighted prioritisation
 - Classification based on IEEE 802.1p
 - Egress rate limiting on each network port

INSTALLATION AND DIAGNOSTIC TOOLS

- ▶ **LED indication**
 - power status
 - wired and wireless link status
 - received signal strength indication
 - TDD sync status
- ▶ **Web GUI tools**
 - antenna alignment tool
 - spectrum analyzer



Um/5X.1000.4x150

Features

ENVIRONMENTAL

- ▶ **Outdoor unit:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN)
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor unit**
 - 0..+40 °C
 - 90-240 VAC ~ @ 50/60 Hz or ±43..±56 VDC
 - power consumption up to 60 W

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN 60950-1:2006, UL 60950-1 2nd ed.
- ▶ **Radio (pending):**
 - EN 301 893 v.2.1.1, EN 302 502, v.2.1.1, FCC part 15.247
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - Directive 2011/65/EU

