


InfiLINK 2x2 R5000-Lmn/32.300.2x200

Description	InfiLINK 2x2 LITE R5000-Lmn/32.300.2x200, 3 GHz point-to-point unit, net throughput up to 180 Mbps, 2x N-type (F) connectors for external antenna
Net throughput	up to 180 Mbps
Recommended distances	75+ km
Radio technology	MIMO 2x2 (OFDM 64/128)
Modulation coding schemes	from BPSK 1/2 to QAM64 5/6
Transmit power	up to 23 dBm
Receiver sensitivity	down to -88 dBm
Frequency range	3100-3400 MHz
Channel width	3.5, 5, 7, 10, 14, 15, 20, 28, 30, 40 MHz
Center frequency adjustment step	125 kHz
Duplex scheme	TDD
Wired Interfaces	2x FastEthernet (PoE out)



InfiLINK 2x2 R5000-Lmn/32.300.2x200

Consumption	up to 15 W				
Power options	110-240 VAC @ 50/60 Hz, +9..56 VDC				
Outdoor Unit (ODU)	240 x 240 x 50 mm, 1.6 kg				
					
Part Number Options	Prefix	Freq. Band	Bitrate	Output Power	Capacity
	<i>R5000-Lmn</i>	<i>32</i>	<i>300</i>	<i>2x200</i>	<i>8</i> <i>20</i> <i>50</i> <i>300</i>
Part Number Example	R5000-Lmn/32.300.2x200 50				
Packing List	<ul style="list-style-type: none"> - Outdoor unit R5000-Lmn/32.300.2x200 - 1 pcs. - Power Supply IDU-CPE-G(24W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland - 2 pcs. - Standard RJ-45 connector - 2 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Cap - 1 pcs. - MONT-KIT-85 Mounting kit - 1 pcs. - Quick Start Guide - 1 pcs. 				



InfiLINK 2x2 R5000-Lmn/32.300.2x200

Features

RADIO

- ▶ Voice/RTP Aware Superpacketing
- ▶ DFS
- ▶ Automatic Bitrate Control
- ▶ Automatic Transmit Power Control
- ▶ TDD synchronization using AUX-ODU-SYNC (excluding Smn/Lmn)
- ▶ Spectrum Analyzer mode
- ▶ Channel testing tools

NETWORKING

- ▶ Ethernet-over-IP and IP-over-IP tunneling
- ▶ ARP protocol support
- ▶ MAC/IP filtering
- ▶ Full-fledged 2nd layer switch
- ▶ RIPv2 / OSPFv2 /static routing
- ▶ L2/L3 Firewall
- ▶ NAT (multipool, H.323-aware)
- ▶ DHCP client/server/relay

MANAGEMENT FEATURES

- ▶ Various Management Protocols: HTTP, HTTPS, Telnet, SSH, SNMP v1/2c/3 (MIB-II and proprietary MIBs)
- ▶ Graphical User Interface
- ▶ LED Indication: power status, wireless and wired link status, signal level
- ▶ Antenna alignment tool
- ▶ Automatic software update
- ▶ Online monitoring with proprietary EMS InfiMONITOR.

QUALITY-OF-SERVICE

- ▶ 17 priority queues
- ▶ IEEE 802.1p support
- ▶ IP TOS / DiffServ support
- ▶ Full voice support
- ▶ Traffic limiting (absolute, relative, mixed)
- ▶ Traffic redirection



InfiLINK 2x2 R5000-Lmn/32.300.2x200

Features

ENVIRONMENTAL

- ▶ **Outdoor Units:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN), 100% humidity, condensing
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor Unit:**
 - 0..+40°C, 95% humidity, non-condensing

SECURITY FEATURES

- ▶ **Storm/flood protection**
- ▶ **Password protection**
- ▶ **Secure command-line access via SSH protocol**

MAC

- ▶ **ARP support**
- ▶ **Proactive channel testing**
- ▶ **Pseudo-radio interface:**
 - unique Infinet Wireless feature to join Infinet networks via 3rd party equipment
- ▶ **Automatic over-the-air firmware upgrade**

STANDARD COMPLIANCE

- ▶ **Radio**
 - ETSI EN 301 893 v.2.1.1
 - ETSI EN 302 502 v.2.1.1
 - FCC Part 15.247
- ▶ **EMC**
 - ETSI EN 301 489-1
 - ETSI EN 301 489-17
 - FCC Part 15 Class B
- ▶ **Safety**
 - ETSI EN 60 950-1:2006
- ▶ **RoHS**
 - Directive 2011/65/EU

