


# Quanta 6 Q6-25

<b>Description</b>	Quanta 6 Q6-25, 6 GHz point-to-point unit, net throughput up to 650 Mbps, integrated dual-pol antenna, 25 dBi, 8x8 deg
<b>Net throughput</b>	up to 650 Mbps
<b>Recommended distances</b>	up to 60 km
<b>Radio technology</b>	MIMO 2x2 (SC-FDE)
<b>Modulation coding schemes</b>	from QPSK 1/4 to QAM256 7/8
<b>Transmit power</b>	up to 27 dBm
<b>Receiver sensitivity</b>	down to -101 dBm
<b>Frequency range</b>	6000-6425 MHz
<b>Channel width</b>	3.5, 5, 7, 10, 14, 15, 20, 28, 30, 40, 50, 56 MHz
<b>Center frequency adjustment step</b>	1 MHz
<b>Duplex scheme</b>	TDD
<b>Antenna</b>	25 dBi
<b>Wired Interfaces</b>	1x Combo port GigabitEthernet/SFP



## Quanta 6 Q6-25

Consumption	up to 15 W
Power options	90-240 VAC ~ @ 50/60 Hz, ±43..56 VDC
Outdoor Unit (ODU)	350 x 350 x 71.5 mm, 2.3 kg
	
Part Number Example	Q6-25/08702
Packing List	<ul style="list-style-type: none"> <li>- Outdoor unit Q6-25 - 1 pcs.</li> <li>- Power Supply IDU-CPE-G(24W) - 1 pcs.</li> <li>- Power Cord - 1 pcs.</li> <li>- Cable Gland INFINET-GLAND-V1 - 1 pcs.</li> <li>- Cable Gland INFINET-GLAND-V2 - 1 pcs.</li> <li>- Standard RJ-45 connector - 1 pcs.</li> <li>- Shielded RJ-45 connector - 1 pcs.</li> <li>- RJ-45 Plug Cap - 1 pcs.</li> <li>- MONT-KIT-85 Mounting kit - 1 pcs.</li> <li>- Quick Start Guide - 1 pcs.</li> </ul>



# Quanta 6 Q6-25

## Features

### RADIO

- ▶ **DFS**
  - ETSI/FCC, including radar detection (including off-channel CAC) and adaptivity
- ▶ **Automatic Bitrate Control**
- ▶ **Automatic Transmit Power Control**
- ▶ **Channel Time Adjustment**

### NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

### MANAGEMENT FEATURES

- ▶ **Various Management Protocols: HTTP, SSH, HTTPS, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)**
- ▶ **Graphical User Interface**
- ▶ **LED Indication: power status, wireless and wired link status, signal level**
- ▶ **Antenna alignment tool**
- ▶ **Automatic software update**
- ▶ **Online monitoring with proprietary EMS InfiMONITOR**

### QUALITY-OF-SERVICE

- ▶ **8 priority queues**
- ▶ **IEEE 802.1p support**
- ▶ **IP DiffServ support**



# Quanta 6 Q6-25

## Features

### ENVIRONMENTAL

- ▶ **Outdoor Units:**
  - operating temperature range  $-40..+60$  °C, (can be extended to  $-55..+60$  °C, models with "t" index in PN), 100% humidity, condensing
  - IP66/IP67 compliant water and dust protection
- ▶ **Indoor Unit:  $0..+40$  °C, 95% humidity, non-condensing**

### SECURITY FEATURES

- ▶ **Storm/flood protection**
- ▶ **Password protection**
- ▶ **Secure command-line access via SSH protocol**

### MAC

- ▶ **VLAN, 802.1ad DVLAN Q-in-Q (pending), 802.1Q (pending)**

### STANDARD COMPLIANCE

- ▶ **Safety:**
  - EN/IEC 62368-1:2018 (pending), EN/IEC 62311:2019 (pending)
- ▶ **Radio:**
  - ETSI EN 302 217-1/-2 (pending)
- ▶ **EMC:**
  - ETSI EN 301 489-1/-4 (pending), FCC Part 15.407 (pending)
- ▶ **RoHS:**
  - RoHS3 EN IEC 63000:2018 (pending)



# Quanta 6 Q6-25

## Radiation diagram

